





Metal Roofing and Siding Accessories

<p style="text-align: center;">STAINLESS GROMMETS</p>  <p>For stitching light transmitting panels together.</p>	<table border="1" style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th style="width: 70%;">DESCRIPTION</th> <th style="width: 30%;">WT./1000</th> </tr> </thead> <tbody> <tr> <td>#6-32 x 1" hole slotted hex head 305 stainless steel machine screw preassembled to 1/2" O.D. washer and neoprene grommet with "molded-in" nut.</td> <td style="text-align: right;">4.9#</td> </tr> <tr> <td colspan="2">✗" diameter hole required.</td> </tr> </tbody> </table>	DESCRIPTION	WT./1000	#6-32 x 1" hole slotted hex head 305 stainless steel machine screw preassembled to 1/2" O.D. washer and neoprene grommet with "molded-in" nut.	4.9#	✗" diameter hole required.					
DESCRIPTION	WT./1000										
#6-32 x 1" hole slotted hex head 305 stainless steel machine screw preassembled to 1/2" O.D. washer and neoprene grommet with "molded-in" nut.	4.9#										
✗" diameter hole required.											
<p style="text-align: center;">VINYL FACED INSULATION</p> 	<table border="1" style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th style="width: 70%;">DESCRIPTION</th> <th style="width: 30%;">WT./MSF</th> </tr> </thead> <tbody> <tr> <td colspan="2">Thickness</td> </tr> <tr> <td>3" (R10)</td> <td style="text-align: right;">192.0#</td> </tr> <tr> <td>4" (R13)</td> <td style="text-align: right;">220.0#</td> </tr> <tr> <td colspan="2">Insulation is UL-25 fire rated, 0.6#/cu.ft. density, with a 4 mil. white vinyl taffeta vapor barrier with 2" vinyl tabs on each side. Length and width of each roll must be specified. Length limits: 20' - 125' Available widths: 3', 4', 5', 6' Maximum 2 widths per order, please! Stock rolls of 3" thick x 6'-0" wide are stocked in 52'-0" and 104'-0" lengths.</td> </tr> </tbody> </table>	DESCRIPTION	WT./MSF	Thickness		3" (R10)	192.0#	4" (R13)	220.0#	Insulation is UL-25 fire rated, 0.6#/cu.ft. density, with a 4 mil. white vinyl taffeta vapor barrier with 2" vinyl tabs on each side. Length and width of each roll must be specified. Length limits: 20' - 125' Available widths: 3', 4', 5', 6' Maximum 2 widths per order, please! Stock rolls of 3" thick x 6'-0" wide are stocked in 52'-0" and 104'-0" lengths.	
DESCRIPTION	WT./MSF										
Thickness											
3" (R10)	192.0#										
4" (R13)	220.0#										
Insulation is UL-25 fire rated, 0.6#/cu.ft. density, with a 4 mil. white vinyl taffeta vapor barrier with 2" vinyl tabs on each side. Length and width of each roll must be specified. Length limits: 20' - 125' Available widths: 3', 4', 5', 6' Maximum 2 widths per order, please! Stock rolls of 3" thick x 6'-0" wide are stocked in 52'-0" and 104'-0" lengths.											
<p style="text-align: center;">POULTRY NETTING</p> 	<table border="1" style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th style="width: 70%;">DESCRIPTION</th> <th style="width: 30%;">WT./EA.</th> </tr> </thead> <tbody> <tr> <td colspan="2">20 Gauge Galvanized x 2" wire mesh</td> </tr> <tr> <td>6' wide x 300' long roll</td> <td style="text-align: right;">88.0#</td> </tr> <tr> <td>6' wide x 150' long roll</td> <td style="text-align: right;">44.0#</td> </tr> </tbody> </table>	DESCRIPTION	WT./EA.	20 Gauge Galvanized x 2" wire mesh		6' wide x 300' long roll	88.0#	6' wide x 150' long roll	44.0#		
DESCRIPTION	WT./EA.										
20 Gauge Galvanized x 2" wire mesh											
6' wide x 300' long roll	88.0#										
6' wide x 150' long roll	44.0#										
<p style="text-align: center;">INSULATION TAPES</p> 	<table border="1" style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th style="width: 100%;">DESCRIPTION</th> </tr> </thead> <tbody> <tr> <td>3" wide White Vinyl Patching Tape x 150' roll (Used for sidelaps or tears in facing.)</td> </tr> <tr> <td>1½" wide Double-Faced Polyester tape x 180' roll (Used to secure insulation at eave or base prior to stitching light.)</td> </tr> </tbody> </table>	DESCRIPTION	3" wide White Vinyl Patching Tape x 150' roll (Used for sidelaps or tears in facing.)	1½" wide Double-Faced Polyester tape x 180' roll (Used to secure insulation at eave or base prior to stitching light.)							
DESCRIPTION											
3" wide White Vinyl Patching Tape x 150' roll (Used for sidelaps or tears in facing.)											
1½" wide Double-Faced Polyester tape x 180' roll (Used to secure insulation at eave or base prior to stitching light.)											